SAINT CITY NATURALS
NON-ENHANCING SEALER

This Non-enhancing Sealer is a heavy duty, water based, silane-siloxane designed to impart water repellency and stain resistance to a wide variety of natural stone, concrete and aggregate surfaces. The silanes react chemically and bond with the substrate to form an insoluble water-resistant treatment within 24-72 hours after application.

Prevents Water Damage | Resists Stains & Mildew | Easy to Apply | Resists Spalling

RECOMMENDED USES: For properly prepared, unsealed natural stone, concrete walls, foundations, pre-cast concrete, block, brick and most aggregate surfaces.

SURFACE PREPARATION: Dirt, grease, grime and any foreign material must be removed before application of this Non-enhancing Sealer. Treat surface for mildew. Oil and grease should be scrubbed with a solution of OxiClean and water.

APPLICATION INFORMATION: Apply with brush, roller, airless sprayer or pump sprayer. When spraying, use a tip designed for gloss coatings. Apply when surface and air temperatures are above 32 Deg. F and rising. Do not apply if the threat of rain exists. Do not over apply or allow product to puddle.

- Always apply a test sample to insure compatibility.
- Do not apply to a surface that was previously treated with another product.
- Take care to cover nearby vegetation, glass, plastic and metals. DP 960 may damage them.
- May be applied to damp surface, however, do not apply when standing water is present.

RECOMMENDED THINNER: This Non-enhancing Sealer does not require thinning and should be used as is, directly from the container.

CLEAN UP: Clean up drips and spills immediately using a damp cloth. Clean tools and equipment with soap and fresh water.

COVERAGE (THEORETICAL): Coverage will depend on porosity and contour of the surface being coated. Coverage typically averages 800 -1,000 square feet per gallon.

BENEFITS:

- Reduces water absorption into the substrate, thus reducing spalling due to freeze thaw and efflorescence, thereby increasing the life of the substrate.
- Colorless and non-yellowing protection preserves the natural appearance of the substrate.
- Penetrating & breathable
- Low VOC
- May be applied to damp surfaces
- May be painted over
- UV Resistant
- Reduces mildew growth on surface

Finish:	**Natural**
Pigment Type:	**None**
Solvent Type:	**Water**
Density:	**8.30 lbs. per gallon**
Viscosity @ 75 deg. F (24 deg. C):	**Waterlike**
Coating VOC:	**<50 g/l**
Flash Point, Minimum:	**Not Flammable**
Flame Spread:	**Class A rating on non combustible substratum**
Estimated Dry Time:	**Touch: 2 hours Recoat: 30 minutes Foot Traffic: 2 hours Vehicular Traffic: 2 hours**

This Non-enhancing Sealer is water based. Do not Freeze.

CAUTION: KEEP OUT OF REACH OF CHILDREN! WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Technical data contained here in is true and accurate at the date of issue, but is subject to change without notice. An RMB representative should be contacted with any questions concerning product information or application procedures. Our products conform to RMB quality standards, but no other warranty is expressed or implied. Liability, if any, is limited to the replacement of product or purchase price.

RMB Inc.
PO Box 400905
Las Vegas, NV 89140
1-888-588-8779
remodelmybackyard.com